

Serial No.: 09/880,779

IN THE SPECIFICATION:

Please enter the attached substitute specification to replace the originally filed specification.

#7 Sub Spec.
1/28/04
C

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

System For Accessing Automatic Control Equipment Via a
Wireless Proximity Network



FIELD OF THE INVENTION

5 The present invention relates to an access system for
accessing automatic control equipment via a wireless proximity
network, using the Bluetooth protocol, for example, from at
least one mobile device or from another automatic control
equipment. This system may be applied to any application
10 belonging to the field of industrial automatic control
systems, building automatic control systems and electrical
distribution network monitoring and control.

BACKGROUND OF THE INVENTION

15 A local connection between automatic control equipment
and a mobile device makes it possible, particularly for
maintenance or operating operators equipped with such a mobile
device, to occasionally access, by means of a man/machine
interface integrated in the mobile device, control, display
20 and monitoring functions, when such operators are located in
proximity to the automatic control equipment to be monitored,

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

i.e. at a distance typically of the order of a few meters. The term "automatic control equipment" hereafter refers to a PLC (Programmable Logic Controller), an input/output module, a regulation device, a monitoring and control station, a man-machine dialogue terminal, an intelligent sensor/actuator or any other equipment related to an automatic control application. The term "mobile device" hereafter refers to a mobile telephone, a laptop computer, a PDA (Personal Digital Assistant), but also any automatic control equipment peripheral liable to be moved, such as a printer.

Such a local connection usually requires an electrical connection via a cable to a connection point either point to point or via a LAN. However, it is not always easy to carry out a reliable wire connection if the automatic control equipment is difficult for the operator to access, either due to an inaccessible geographic location or for access safety reasons (tightness, harmful atmosphere). In addition, in the long-term, repeated connections and disconnections of mobile devices may damage connection points.

Another requirement consists of wanting to make a local connection between several items of automatic control

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

equipment, for example, if one or more items of automatic control equipment are embedded on a mobile support, such as a truck, travelling crane, etc. According to the location of the mobile support, it is required to have such mobile automatic
5 control equipment communicate occasionally with other automatic control equipment located in proximity for example for control and monitoring functions (transmission of orders and instructions, reception of reports, etc.).

Wireless connections produced using infrared technology
10 already exist. However, these connections are directional and may be interrupted as soon as an obstacle is located between the transmitter and the receiver, which reduces their interest in certain automatic control applications. A rapid, reliable and easy-to-implement proximity connection would therefore be
15 considered as significant progress for operating and maintenance operations on automatic control equipment. For this reason, a radio wave technology would enable improved connection reliability.

In addition, to enable communication with automatic
20 control equipment and mobile devices of very diverse origins, it would be desirable to have a standard technology enabling a

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

large number of different devices to detect and identify each other automatically for a user. The Bluetooth protocol is a radio wave high-speed wireless proximity technology. This technology, derived from the world of telecommunications and
5 information technology, comes from the "Bluetooth SIG" (Special Interest Group) and enables communication between several devices located at a distance of the order of ten meters from each other (excluding repeaters and according to the state of the art). It does not require configuration since
10 any device within the field covered by a proximity network is automatically detected and synchronised with the other devices connected to this proximity network in order to be able to communicate.

Therefore, it would be of interest to use this technology
15 in the field of automatic control systems to provide a solution for the above-mentioned problems, i.e., provide a rapid connection from a mobile device particularly for operating and maintenance operations on automatic control equipment or provide a rapid connection between several items
20 of automatic control equipment for control and monitoring functions.

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

In this way, using the invention, an operating or maintenance operator, managing for example several autonomous items of automatic control equipment located at different locations, could rapidly access each item of automatic control equipment from a mobile device without needing an electrical connection and without a specific procedure, thus facilitating such operator's work.

Similarly, automatic control equipment, particularly automatic control equipment embedded in installations liable to be moved, could easily communicate with each other (occasionally or not according to their relative location), using an access system according to the invention, enabling them to detect and identify each other transparently with respect to automatic control application programs, so as to be able to exchange messages and information.

SUMMARY OF THE INVENTION

For this reason, the invention relates to an access system between an automation equipment server, which integrates transmission/reception means to transmit and receive messages on a wireless proximity network using radio

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

wave technology and at least one mobile device or at least one client automation equipment. This access system is characterized in that the server automatic control equipment comprises server communication means capable of implementing a link mechanism in compliance with the Bluetooth protocol with communication means of a mobile device or with client communication means of a client automation equipment, in order to supply control, display and monitoring functions from the server automatic control equipment, wherein the link mechanism comprises a detection phase, a description phase and a service phase.

The client communication means or the server communication means of automatic control equipment have access to an internal memory containing information relating to the automatic control equipment. According to a characteristic of the invention, the same automatic control equipment may comprise both server communication means and client communication means.

The invention also relates to an automatic control equipment, wherein it communicates on a proximity network by

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS
Serial No.: 09/880,779

means of an access system according to any of the above claims.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Other characteristics will be seen in the following detailed description referring to an embodiment given as an example and represented in the appended figures wherein:

 - figure 1 represents an example of architecture of the access system described in the invention between a mobile
10 device and an automation equipment server,

 - figure 2 represents another example of architecture of the access system described in the invention between client automation equipment and an automation equipment server,

 - figure 3 is a schematic representation of the
15 different possible types of messages,

 - figure 4 represents automatic control equipment which is both client and server.

DETAILED DESCRIPTION

20 In figure 1, an automation equipment server 20 comprises transmission/reception means 25, connected to server

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

communication means 27, themselves able to access an internal memory 28 of data from the server automatic control equipment 20. This internal memory 28 which particularly contains information relating to the status of the server automatic control equipment 20 and the representative variables of an automatic control application controlled by the automatic control equipment. It is also accessible to an automatic control application program 29 which can run in the server automatic control equipment 20 to control and monitor an automatic control application. It is thus possible to exchange information between the application program 29 and the server communication means 27. The transmission/reception means 25 are in charge of transmitting and receiving messages on a wireless proximity network 30, using a radio wave technology supporting the Bluetooth protocol. Therefore, the transmission/reception means 25 integrate the components required for the operation of the Bluetooth protocol particularly a Bluetooth chipset.

The server communication means 27 are capable of implementing a link mechanism with communication means 16 of at least one mobile device 10. Such mobile device 10 comprises

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

transmission/reception means 15 to transmit and receive messages on the proximity network 30, connected to the communication means 16. The mobile device 10 also comprises a man-machine interface 19, which includes for example a keyboard or a screen, using which a user of the mobile device 10 can send queries and display responses.

Sub C1
Figure 2 shows an automation equipment server 20 linked by a proximity network 30 to client automation equipment 20', comprising transmission/reception means 25' in charge of transmitting and receiving messages on a wireless proximity network 30, using a radio wave technology supporting the Bluetooth protocol. Such transmission/reception means 25' are connected to client communication means 26', themselves able to access an internal data memory 28'. Such internal memory 28' which particularly contains information relating to the status of the server automatic control equipment 20' and the representative variables of an automatic control application controlled by the automatic control equipment. It is also accessible to an automatic control application program 29' which can run in the server automatic control equipment 20' to control and monitor an automatic control application. It is

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

thus possible to exchange information between the application
program 29' and the client communication means 26'. In
addition, the server communication means 27 are capable of
implementing a link mechanism with the client communication
5 means 26' of at least one item of client automation equipment
20'.

Automatic control equipment has a server function when it
is able to receive and respond to a query sent by a client (in
this case, this equipment may be referred to as a server).
10 Conversely, automatic control equipment has a client function
when it is able to send a query to a server and receive the
response from the server (in this case, this equipment may be
referred to as a client).

To set up a link mechanism, a client (i.e. a mobile
15 device 10 and client automation equipment 20') firstly enters
the detection phase to try to detect the presence of at least
one server (i.e. an automation equipment server 20) in the
field of action 31 of the proximity network 30. For this, with
reference to figure 3, the communication means of a client 16,
20 26' generate a detection query 11. In the case of client
automation equipment 20', this detection query 11 is generated

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

by the communication means 26' at regular intervals, at the operator's request, or following an order from the application program 29'.

5 The server communication means 27 are continuously capable of receiving a detection query 11. Upon reception of such a query, they generate a detection response 21 used to signal to the sender of the query 11 the presence of an automation equipment server 20 in the field of action 31 of the proximity network 30.

10 Upon reception of such detection response 21, the client 10, 20' continues to set up the link mechanism by initiating the description phase wherein the communication means of a client 16, 26' generate a description query 12 intended for the server automatic control equipment 20 that responded to
15 the detection query 11. When it receives such description query 12, it returns a description response 22 which may include an identification and authentication of the server automatic control equipment 20, and a list of the services offered which will be accessible to the client(s).

20 According to the type of server automatic control equipment 20, the services offered to the user of a mobile

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

device 10 or to the application program 29' of client automation equipment 20' particularly comprising application program loading and unloading, reading and writing of internal variables and inputs/outputs, monitoring statuses and faults, 5 controlling part or all of the automatic control equipment, etc., thus providing control, display and monitoring functions of the server automatic control equipment 20. All these services may clearly comprise a secure access using passwords, identification keys, or other suitable means.

10 When the detection response 22 from the server automatic control equipment 20 is received by the client 10, 20', the link mechanism is set up and the service phase is started. At the request of a user of a mobile device 10 and according to the services offered, the communication means 16 may generate 15 service queries 13 to the server automatic control equipment 20 and wait for the corresponding service responses 23. Similarly, at the request of the application program 29' of client automation equipment 20' and according to the services offered, the client communication means 26' may also generate 20 service queries 13 to the server automatic control equipment 20 and wait for the corresponding service responses 23.

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

Automatic control equipment such as that described in the invention can simultaneously have a server function and a client function. For this, it must comprise server communication means 27' and client communication means 26',
5 able to access the internal memory 28', as shown in figure 4. In this example, automatic control equipment 20' has a server function 32 in relation to a mobile device 10, while also having a client function 33 in relation to other server automatic control equipment 20.

10 Other examples of use of the present invention can be envisaged. For example, the front panel of automatic control equipment frequently comprises signalling means such as LEDs or digital displays. However, when automatic control equipment cannot be installed in the visual field of an operator located
15 in proximity, their signalling means lose their purpose. In addition, installing display means on all automatic control equipment is a costly solution, since they are only useful in the presence of an operator. Using the present invention, it is therefore possible to envisage a portable display device
20 serving as a mobile client device and enabling an operator

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

equipped with such a device to replace signalling means when in proximity to an automatic control equipment server.

More generally, the invention may also be used to centralise various peripherals, such as a keyboard, a printer, etc., for occasional shared use between several of remote server automatic control equipment. When operators wish to use a particular peripheral in connection with a given server automatic control equipment, they simply position such peripheral in proximity to the server automatic control equipment for the required operating time, which avoids electrical connections and makes it possible to optimise the number of peripherals in this way.

Naturally, without leaving the scope of the invention, it is possible to envisage other variants and perfection of details and even the use of equivalent means.

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

CLAIMS

1. (Currently Amended) An access system comprising:
an server automatic control equipment comprising:
5 transmission/reception means for transmitting and
receiving messages on a wireless proximity network using radio
waves,
a link mechanism, and
server communication means for linking with a receiving
10 means; and
at least one mobile device comprising communication means
for linking with said server communication means, or at least
one client automatic control equipment comprising client
communication means for linking with said server communication
15 means, wherein
said server communication means is also for implementing
said link mechanism in compliance with the Bluetooth protocol
with said communication means of said mobile device or with
said client communication means, to supply control, display
20 and monitoring functions from the server automatic control
equipment,

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

the link mechanism comprising a detection means for detecting presence of at least one server automatic control equipment,

a description means for querying identification of said
5 detected server automatic control equipment, and

a service means for communicating with said identified server automatic control equipment.

2. (Currently Amended) The access system according to
10 claim 1, further comprising an internal memory containing information relating to the server automatic control equipment, wherein the client communication means or the server communication means has access to the internal memory.

15 3. (Currently Amended) The access system according to claim 2, wherein said client automatic control equipment comprises server communication means and client communication means, for performing a server function and a client function.

20 4. (Currently Amended) The access system according to claim 2, wherein the server communication means of a server

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS
Serial No.: 09/880,779

automatic control equipment is for waiting for a detection query sent by at least one mobile device or at least one client automatic control equipment on the proximity network.

5 5. (Currently Amended) The access system according to claim 4, wherein the server communication means is for generating a detection response used to signal presence of the server communication means to the mobile device or the client automatic control equipment, following reception of a
10 detection query sent from the mobile device or from the client automatic control equipment.

6. (Currently Amended) The access system according to claim 2, wherein the client communication means of a client
15 automatic control equipment is for transmitting detection queries across the proximity network to detect the presence of at least one server automatic control equipment within the proximity network.

20 7. (Currently Amended) The access system according to claim 6, wherein the client communication means is for

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

transmitting detection queries at regular intervals or at the initiative of an application program running in the client automatic control equipment.

5 8. (Currently Amended) The access system according to claim 5, wherein the server communication means is for responding to a description query transmitted by the mobile device or by the client automatic control equipment by returning a description response which includes an
10 identification and authentication of the server automatic control equipment and a list of services offered by the server automatic control equipment.

9. (Currently Amended) The access system according to
15 claim 8, wherein the server automatic control equipment is for exchanging messages with the mobile device via the proximity network when the link mechanism establishes a link, so that a user of the mobile device can perform control, display and monitoring functions of the server automatic control
20 equipment.

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

10. (Currently Amended) The access system according to claim 8, wherein the server automatic control equipment is for exchanging messages with the client automatic control equipment via the proximity network when the link mechanism
5 establishes a link, so that an application program running in the client automatic control equipment can perform control, display and monitoring functions of the server automatic control equipment.

10 11. (Currently Amended) The access system of claim 1 in combination with an automatic control equipment, comprising automatic control equipment comprising means for communicating over a proximity network by means of said access system.

SUBSTITUTE SPECIFICATION WITHOUT MARKINGS

Serial No.: 09/880,779

ABSTRACT

An access system between an automation equipment server,
which integrates transmission/reception means to transmit and
receive messages on a wireless proximity network using a radio
wave technology in compliance with the Bluetooth protocol, and
5 at least one mobile device or at least one client automation
equipment. An automation equipment server comprises server
communication means to implement a link mechanism in order to
supply control, display and monitoring functions of the server
automatic control equipment from a mobile device or an
10 automatic control equipment.